



PCM-1000 Series Pre-Wired Power Control Boxes (NEMA 12 Indoor Use)



16 Amp Rating

- * TEC-9100 PID temperature control
- * Standard size thermocouple jack
- * 5-foot, 3-conductor line cord
- * 20A straight-blade heater receptacle with ground
- * Fused at 20A
- * 25A mechanical relay
- * Enclosure Dimensions: 6"H x 6"W x 6"D
- * Wall mounting slots: 4" centers side to side, 6-3/4" centers top to bottom
- * Agency Approval:



Part Number PCM10001

- * Voltage: 120 VAC (1 Phase)
- * Maximum Wattage: 1920 W
- * Temperature Range: 0-1200°F
- * Type J thermocouple jack

Part Number PCM10002

- * Voltage: 240 VAC (1 Phase)
- * Maximum Wattage: 3840 W
- * Temperature Range: 0-1200°F
- * Type J thermocouple jack

Part Number PCM10003

- * Voltage: 120 VAC (1 Phase)
- * Maximum Wattage: 1920 W
- * Temperature Range: 0-2400°F
- * Type K thermocouple jack

Part Number PCM10004

- * Voltage: 240 VAC (1 Phase)
- * Maximum Wattage: 3840 W
- * Temperature Range: 0-2400°F
- * Type K thermocouple jack



24 Amp Rating

- * Temperature Range: 0-2400°F
- * TEC-9100 PID temperature control
- * NO-NC alarm contacts
- * Terminal blocks for incoming power, heater power and universal sensor
- * 32A magnetic contactor
- * BX connectors for sensor, incoming & heater leads
- * Disconnect & 30A heater fusing to be supplied by customer
- * Agency Approval:



Part Number PCM10005

- * Voltage: 240 VAC (1 or 3 Phase)
- * Maximum Wattage: 5760 or 9970 W
- * Enclosure Dimensions: 10"H x 10"W x 6"D
- * Wall mounting slots: 8" centers side to side, 10-3/4" centers top to bottom

Part Number PCM10006

- * Voltage: 480 VAC (1 or 3 Phase)
- * Maximum Wattage: 11,520 or 19,930 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom



48 Amp Rating

- * Temperature Range: 0-2400°F
- * TEC-9100 PID temperature control
- * NO-NC alarm contacts
- * Terminal blocks for incoming power, heater power and universal sensor
- * 65A magnetic contactor
- * BX connectors for sensor, incoming & heater leads
- * Disconnect & 60A heater fusing to be supplied by customer
- * Agency Approval:



Part Number PCM10007

- * Voltage: 240 VAC (1 or 3 Phase)
- * Maximum Wattage: 11,520 or 19,930 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom

Part Number PCM10008

- * Voltage: 480 VAC (1 or 3 Phase)
- * Maximum Wattage: 23,000 or 39,900 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom