

TEC-7400 3/16din Temperature Controller

Design Features



- * 3/16 DIN size – 72 mm × 72 mm
- * Fuzzy modified PID heat and cool control
- * Universal input (TC, PT100, mA, V) with high accuracy 18-bit D-A
- * Countdown display
- * RS - 485 and Analog Retransmission Available
- * Micro USB Programming Port
- * Fast sampling rate (200 msec)
- * Manual control & auto-tune function
- * Wide range of alarm mode selection
- * Lockout protection
- * Bumpless transfer during failure mode
- * Soft-start ramp & dwell timer
- * Bright LCD display stabilized with digital filter
- * High performance with low cost

Agency Approvals:



RoHS, REACH, WEEE

Hardware Code: TEC-7400 -

A Part Number based on the hardware code and any software pre-programming will be issued at time of order.

Standard lead time is stock to 2 weeks.

Power Input BOX 1

- 4** = 90-250 VAC
- 5** = 11-40 VDC / 20-28 VAC

Output 1 BOX 2

- 1** = Relay: 2A / 240 VAC
- 2** = Pulse DC for SSR drive: 5 VDC (30 mA max)
- 3** = Isolated, 4-20 mA (default), 0-20 mA
- 5** = Isolated VDC, 0-10 scalable
- C** = Pulse DC for SSR drive: 14 VDC (40 mA max)

Output 2 / Alarm 1 BOX 3

- 0** = None
- 1** = Relay: 2A / 240 VAC
- 2** = Pulse DC for SSR drive: 5 VDC (30 mA max)
- 3** = Isolated, 4-20 mA (default), 0-20 mA
- 5** = Isolated, VDC, 0-10 scalable
- C** = Pulse DC for SSR drive: 14 VDC (40 mA max)

Alarm 2 to 3 BOX 4

- 0** = None
- 1** = Alarm 2: Relay: 2A / 240 VAC
- 2** = Alarm 2 and 3: Relays: 2A / 240 VAC

Event Inputs BOX 5

- 0** = None
- 1** = 6 Event Inputs

Option 1 BOX 6

- 0** = None
- 1** = RS-485 Interface & Remote Setpoint

Option 2 BOX 7

- 0** = None
- 1** = 1 CT Input and Remote Setpoint
- 2** = 2 CT Inputs and Remote Setpoint

Option 3 BOX 8

- 0** = None
- 1** = Retransmit: 4-20 mA / 0-20 mA and Remote Setpoint
- 2** = Retransmit: 0-10 VDC and Remote Setpoint
- 3** = Alarm 4 Relay: 2A / 240 VAC and Remote Setpoint

Option 4 BOX 9

- 0** = None
- 1** = Terminal Covers
- 2** = Ramp and Soak Firmware
- 3** = Terminal Covers and Ramp and Soak Firmware

**Transformer for
Heater Break Alarm**
(0-50 Amp current)
Part Number: TEC99998

Stock and Common Part Numbers

(All Stock Part Numbers Include Terminal Covers)
(Default Type "J" Thermocouple Input)

Part Number	Output 1	Out 2/ Alm 1	Option 1
TEC45001	Relay	None	None
TEC45002	Relay	Relay	None
TEC45003	Relay	Relay	(2) Rel
TEC45004	Pulse DC	None	None
TEC45005	Pulse DC	Relay	None
TEC45006	Pulse DC	Relay	(2) Rel
TEC45007	4-20mA	none	none
TEC45008	4-20mA	Relay	(2) Rel

SOUTHWEST HEATER AND CONTROLS

10610 Control Place, Dallas Texas 75238

Main# 214-340-7500

Toll Free#: 800-687-2220

EMAIL: sales@swhc.com

WEB: www.swhc.com

TEC-7400 Specifications

Power Input

Standard: 90-250 VAC, 47-63 Hz, 12VA, 6W maximum
Optional: 11-40 VDC / 20-8 VAC, 47-63 Hz, 12VA, 6W maximum

Signal Input

Resolution: 18 Bits
Sampling Rate: 5 Times / Second (200msec)
Maximum Rating: -2VDC minimum, 12VDC maximum
Sensor Break Detection: Sensor open for thermocouple and RTD inputs, sensor short for RTD input, below 1mA for 4-20mA input, below 0.25V for 1-5V input, not available for other inputs
Sensor break responding time: Within 4 seconds for thermocouple and RTD inputs, 0.1 second for 4-20mA and 1-5V inputs

Remote Set Point Input

Type: Linear current, Linear voltage
Range: -3-27mA, -1.3-11.5V **Accuracy:** $\pm 0.05\%$
Input Impedance: Current: 2.5 Ω , Voltage: 1.5M Ω
Resolution: 18 bits **Sampling Rate:** 1.66 times/second
Maximum Rating: 280mA maximum for current input, 12VDC maximum for voltage input
Temperature Effect: $\pm 1.5\mu V / ^\circ C$ for voltage input, $\pm 3.0\mu V / ^\circ C$ for current input
Sensor Break Detection: Below 1mA for 4-20mA input, below 0.25V for 1-5V input, not available for other inputs

Event Input

Number of Event Inputs: 2
Logic Low: -10V minimum, 0.8V maximum
Logic High: 2V minimum, 10V maximum

CT Input

CT type: CT98-1
Accuracy: $\pm 2\%$ of full scale reading, ± 1 digit maximum
Input Impedance: 294 Ω
Measurement Range: 0-50A AC
Output of CT: 0-5V DC
CT Mounting: Wall (Screw) mount
Sampling Rate: 1 time/second

Output 1 /Output 2

Type: Relay, pulsed voltage, linear voltage and linear current
Relay Rating: 2A, 240V AC, 200000 life cycles for resistive load
Pulsed Voltage: Source voltage 5V, Current limiting resistance 66 Ω
Linear Output Resolution: 15 Bits
Isolation Breakdown Voltage: 1000 V AC
Load Capacity of Linear Output: Linear current: 500 Ω maximum, Linear voltage: 10K Ω minimum

Alarm

Relay Type: Form A
Maximum Rating: 2A, 240VAC, 200000 life cycles for resistive load
Alarm Functions: Dwell timer, Deviation low, Deviation high, Deviation band low, Deviation band high, Process high, Process low
Alarm Mode: Latching, Hold, Normal, Latching/Hold
Dwell Timer: 0.1-4553.6 minutes

Data Communications

Interface: RS-485 **Protocol:** Modbus RTU
Address: 1-247 **Baud Rate:** 2.8 - 115.2 Kbits/sec
Parity Bit: None, Even or Odd **Stop Bit:** 1 or 2 Bits
Data Length: 7 or 8 Bits **Communication Buffer:** 160 bytes

Analog Retransmission

Output Signal: 4-20 mA, 0-20 mA, 0-10V
Resolution: 15 Bits **Accuracy:** $\pm 0.05\%$ of span $\pm 0.0025\%$ / $^\circ C$
Load Resistance: 0-500 Ω for current output, 10K Ω minimum for voltage output
Isolation Breakdown: 1000VAC minimum
Integral Linearity Error: $\pm 0.005\%$ of span
Linear Output Ranges: 0-22.2mA (0-20mA / 4-20mA), 0-5.55V (0-5V, 1-5V), 0-11.1V (0-10V)

User Interface

Keypad: 4 Keys **Display Type:** 4 digit LCD display
No. of Display: 3 **Upper Display Size:** 0.58" (15mm)
Lower Display Size: 0.32" (8.3mm)

Programming Port

Interface: Micro USB
PC Communication Function: Automatic Setup, Calibration and Firmware Upgrade

Control Mode

Output 1: Reverse (Heating) or Direct (Cooling) Action
Output 2: PID cooling control, Cooling P band 50~300% of PB, Dead band -36.0 ~ 36.0 % of PB
ON-OFF: 0.1-90.0 ($^\circ F$) hysteresis control (P band = 0)
P or PD: 0-100.0 % offset adjustment
PID: Fuzzy logic modified Proportional band 0.1 ~ 900.0 $^\circ F$, Integral time 0-3600 seconds, Derivative time 0-360.0 seconds
Cycle Time: 0.1-90.0 seconds
Manual Control: Heat (MV1) and Cool (MV2)
Failure Mode: Auto transfer to manual mode while sensor break or A-D Converter damage
Ramping Control: 0 to 900.0 $^\circ F$ / Minute or 0 to 900.0 $^\circ F$ / Hour Ramp Rate


Profiler

Availability: Option **No. of Segments / Program:** 4 / 8 / 16

Environmental and Physical Specifications

Operating Temperature: -10 $^\circ C$ to 50 $^\circ C$
Storage Temperature: -40 $^\circ C$ to 60 $^\circ C$
Humidity: 0 to 90 % RH (Non-Condensing)
Insulation Resistance: 20M Ω minimum (@500V DC)
Dielectric Strength: 2000V AC, 50/60 Hz for 1 Minute
Vibration Resistance: 10 to 55 Hz, 10m/s² for 2 Hours
Shock Resistance: 200 m / s² (20g)
Moldings: Flame retardant polycarbonate
Mounting: Panel
Dimensions W x H x D: 2-27/32 x 2-27/32 x 2-3/8" (72 x 72 x 59 mm)
Depth Behind Panel: 2" (50 mm)
Cut Out Dimensions: 2-11/16 x 2-11/16" (68 x 68 mm)
Weight: .41 lbs. (190 g)

Rear Terminal Connections



SOUTHWEST HEATER AND CONTROLS

10610 Control Place, Dallas Texas 75238

Main# 214-340-7500

Toll Free#: 800-687-2220

EMAIL: sales@swhc.com

WEB: www.swhc.com